Wired / Wireless Print Server

PS-3207U / UWg

3 Ports Wired / Wireless Print Server

2 x USB 2.0 + 1 x Parallel Ports

RoHS Compliant

Taiwan / Headquarters
Edimax Technology Co., LTD.
TEL:886-2-7739-6888
FAX:886-2-7739-6887
sales@edimax.com.tw

China
Beijing Edimax Science & Technology Co., LTD.
TEL:8610-6213-9288
FAX:8610-6213-9231
sales@edimax.com.cn

Europe
Edimax Technology Europe B.V.
TEL:31-499-377344
FAX:31-499-372647
sales@edimax.nl

Latin America
TEL:1-786-845-8099
FAX:1-786-331-8490
sales_latinamerica@edimax.com

Poland
Edimax Technology Europe B.V. SP. Z O.O.
Tel: +48(22)-6060-255
Fax: +48(22)-6060-254
sales@edimax.nl

U.S.A.
Edimax Computer Company
TEL:1-408-496-1105
FAX:1-408-980-1530
sales@edimax.com

U.K.
Edimax Technology (UK) Ltd.
TEL:44-870-7740226
FAX:44-870-7740227
info@edimax.co.uk

Easy Installation and Configuration (Web Based)

The print server's easy-to-use windows installation wizard enables a quick installation and setup. The print server can also be conveniently configured from any network client that supports web-browsing.

Supports Peer-to-Peer and Server-Based Printing

Supports both Peer-to-Peer and Server-based printing. LAN clients can connect directly with the print server to execute printing jobs (Peer-to-Peer printing); or they can send printing tasks to a server first (queuing jobs) and allow the server to connect with the print server to execute the printing jobs (Server-based printing).

Provides Complete Printing Methods

The print server provides LPR, IPP, Raw Printing and Unix Logical Printer printing methods. You can choose the best printing method that is suitable for your environment.

Supports Major Operating Systems

The print server is compatible with all major operating systems used today, for example Windows 98SE / Me / NT / 2000 / XP / 2003, NetWare 3.x above, MAC OS and Unix/Linux environments.

Supports DHCP Server/Client

The printer server can act as a DHCP server, allowing your LAN clients to automatically obtain an IP address or it can act as a DHCP client allowing a easy integration to your existing network.

Support USB 2.0 High Speed

This print server supports USB 2.0 High Speed which increases the throughput when connected to USB 2.0 printers.

Wired / Wireless Print Server

Taiwan / Headquarters
Edimax Technology Co., LTD.
TEL:886-2-7739-6888
FAX:886-2-7739-6887
sales@edimax.com.tw

China
Beijing Edimax Science & Technology Co., LTD.
TEL:8610-6213-9288
FAX:8610-6213-9231
sales@edimax.com.cn

Europe
Edimax Technology Europe B.V.
TEL:31-499-377344
FAX:31-499-372647
sales@edimax.nl

Latin America
TEL:1-786-845-8099
FAX:1-786-331-8490
sales_latinamerica@edimax.com

Poland
Edimax Technology Europe B.V. SP. Z O.O.
Tel: +48(22)-6060-255
Fax: +48(22)-6060-254
sales@edimax.nl

U.S.A.
Edimax Computer Company
TEL:1-408-496-1105
FAX:1-408-980-1530
sales@edimax.com

U.K.
Edimax Technology (UK) Ltd.
TEL:44-870-7740226
FAX:44-870-7740227
info@edimax.co.uk

Features

- Complies with IEEE 802.3, 802.3u, 802.11b and 802.11g standards.
- Provides two USB 2.0 ports and one parallel port to connect to the printer.
- Supports 64/128-bit WEP data encryption and WPA-PSK (TKIP and AES) wireless security.
- Shares printer with multiple PCs through 10/100Mbps wired or IEEE 802.11g/b wireless network.
- Supports TCP/IP, NetBEUI, IPX/SPX, Rendezvous and AppleTalk network protocols.
- Supports LPR, IPP, Raw Printing and Unix Logical printing protocols.
- Supports Peer-to-Peer Printing and Server-based printing.
- Compatible with all major operating systems (Windows 98SE/Me/NT/ 2000/XP/2003, NetWare 3.x above, MAC OS and Unix/Linux.
- Supports Web-based management and Windows Configuration Utility.
- Supports DHCP Server and Client protocols.
- Supports IPv6 protocol
- Features an easy-to-use installation and configuration programs.
- Firmware upgradeable.

Specification

Model NO.	PS-3207UWg	I	PS-3207U
Interface	802.11g WLAN	I	10/100Base-TX
CPU	RISC CPU		
Flash	2MB NOR Flash		
RAM	16MB SDRAM		
USB Port	USB 2.0 Type A x 2, DB-25 x 1		
LAN Port	10/100M UTP Port x 1 (Auto-MDI/MDI-X)		
Output Power	16dBm-18dBm		
Power	12VDC, 1A Linear Power Adapter		
Dimension	30(H) x 187(W) x 100(D) mm		
Temperature	0~55°C		
Humidity	10~90% (Non-Condensing)		
Certification	FCC, CE		

EDIMAX
NETWORKING PEOPLE TOGETHER